تقرير معايير جودة الخدمة لشركة الاتصالات السعودية

Report on stc Quality of Service Indicators







		General Key Performance Indicator	rs ·					
Measurement KPI value								
KPI name	Unit	Required Statistics and description	1st month	2nd month	3rd month	1st Quarter	Target value for quarter	
		· · · · · · · · · · · · · · · · · · ·		0.2	0.4	0.2		
Supply Time	Time -	fastest 50 % of orders are completed (in days)	0.1	0.7	0.4			
		fastest 90 % of orders are completed (in days) fastest 95 % of orders are completed (in days)	0.6	0.7	1	0.7	7 days for 90% of requests	
		fastest 99 % of orders are completed (in days)	0.7	1.1	1.3	1.1		
	Percentage %	percentage of fault reports per fixed access line	3.27%	3.19%	3.62%	3.36%		
Fault Rate	Number	average number of fixed access lines	1854362	1866681	1879626	1,866,890	< 5%	
	Number	fastest 80 % of repairing valid faults on fixed access lines(in hours)	11.71	13.17	14.25	13.04	- Within 24 hours	
Fault Repair Time	Time	fastest 90 % of repairing valid faults on fixed access lines(in hours)	15.49	17.69	21.15	18.11		
raut Repair Time	IIII	fastest 95 % of repairing valid faults on fixed access lines(in hours)	20.81	24.30	30.00	25.04	for 90% of faults	
		The average time to respond to requests received through electronic channels,						
		including e-mail, social media and others (in hours)	0:00:12	0:00:27	0:01:18	0:00:41		
Response Time for	Time	The average time to respond to requests received through voice calls (in seconds)	0:00:17	0:00:16	0:00:32	0:00:21	within 60 sec	
Reply to Requests	Time	Time to respond to the fastest 85% of requests received through voice calls					for 85% of voice calls	
		(in seconds)	0.48	0.16	1.99	0.85		
		Key Performance Indicators Applied on Fixed	l Network	S				
KPI name	Measurement	rement KPI value				Target value for quarter		
Krillallie	method	Required Statistics and description	1st month	2nd month	3rd month	1st Quarter	raiget value for quarter	
	Percentage %	unsuccessful calls for national calls	0.15%	0.11%	0.11%	0.123%		
T CLCUD		unsuccessful calls for international calls	0.60%	0.89%	0.67%	0.720%	2 10%	
Unsuccessful Call Ratio	N 1	Total number of national calls	50,952,580	47,571,182	47,421,587	48,648,450		
	Number	Total number of International calls	2,701,458	2,480,258	2,603,495	2,595,070		
Dropped Call Rate	Percentage %	dropped calls, calculated from all the calls in the period	0.10%	0.11%	0.10%	0.103%	< 1%	
	Time	The mean value of call setup time for national calls (in seconds)	1.26	1.28	1.2	1.247		
		The time in which the fastest 95 % of national calls are set-up (in seconds)	1.05	1.08	0.99	1.040	/	
		The time which the fastest 99% of national calls are set-up (in seconds)	1.21	1.23	1.15	1.197	95 % in < 7 sec;	
Call Setup Time		The mean value of call setup time for international calls (in seconds)	1.12	1.15	1.07	1.113		
Can Setup Time		The time which the fastest 95 % of international calls are set-up (in seconds)	0.86		0.81	0.847	99% in <10 sec	
		The time which the fastest 99 % of international calls are set-up (in seconds)	1.05		1.02	1.053		
	Number	The total number of national calls	50,952,580	47,571,182	47,421,587	48,648,450		
	rumoci	The total Number of international calls	2,701,458	2,480,258	2,603,495	2,595,070		
Speech Connection Quality	Mean Opinion Score(MOS)	This value is obtained through special tool that analyzes the sound after it is transferred between the two ends of the connection	3.93	3.92	3.9	3.92	> 3,75 MOS	
		Key Performance Indicators Applied on Mobil	e Networl	ζS				
A. OSS Counters Measurments								
	Measurement KPI value							
KPI name	method	Required Statistics and description	1st month	2nd month	3rd month	1st Quarter	Target value for quarter	
Unsuccessful Call Ratio	Percentage %	Unsuccessful calls, calculated from all the call attempts in the period	0.26%	0.26%	0.24%	0.26%	< 1%	
Dropped Call Ratio	Percentage %	dropped calls, calculated from all the calls in the period	0.24%	0.24%	0.23%	0.24%	< 1%	
Dropped Can Kano	I di centage /0		4.80	4.60	4.92	4.77	95 % in < 7 sec;	
		The mean value of call setup time (in seconds)						
	Time	The mean value of call setup time (in seconds) The time which the fastest 95 % of calls are set-up (in seconds)					, , , , , , , , , , , , , , , , , , , ,	
Call Setup Time	Time	The mean value of call setup time (in seconds) The time which the fastest 95 % of calls are set-up (in seconds) The time which the fastest 99 % of calls are set-up (in seconds)	4.14 4.57	3.95 4.38	4.27 4.70	4.12 4.55	99% in <10 sec	

	Key Performance Indicators Applied to Internet Access (Fiber)					
Package	KPI name	Measurement	KPI value		Target value for quarter	
		method	Required Statistics and description	Q1	0 1	
		Mbps	The highest 95 % of download speed	90.25		
			The lowest 5 % of download speed	69.73		
			The mean value of download speed	89.21		
			The median value of download speed	92.24		
	Data Transmission Speed		The standard deviation of download speed	10.06	None	
B	Data Transmission Speed		The highest 95 % of upload speed	19.85	None	
100 MB			The lowest 5 % of upload speed	14.19		
0			The mean value of upload speed	19.58		
10			The median value of upload speed	19.41		
			The standard deviation of upload speed	3.61		
	Unsuccessful Data Transmission Ratio	Percentage %	Percentage of unsuccessful data transmission (in \mathbf{x}^{10-3})	cannot be provided	None	
	Delay (One-way	Time	The mean values of the delay (in milliseconds)	12.72	None	
	transmission time)		The standard deviation of the delay (jitter) (in milliseconds)	88.37		
	Data Transmission Speed	Mbps	The highest 95 % of download speed	174.64		
			The lowest 5 % of download speed	136.27	None	
			The mean value of download speed	172.70		
			The median value of download speed	176.28		
200 MB			The standard deviation of download speed	21.74		
			The highest 95 % of upload speed	69.73		
			The lowest 5 % of upload speed	50.98		
			The mean value of upload speed	68.83		
			The median value of upload speed	70.43		
			The standard deviation of upload speed	9.23		
	Unsuccessful Data Transmission Ratio	Percentage %	Percentage of unsuccessful data transmission (in \mathbf{x}^{10-3})	cannot be provided	None	
	Delay (One-way	Time	The mean values of the delay (in milliseconds)	10.70	None	
	transmission time)	Tillic	The standard deviation of the delay (jitter) (in milliseconds)	101.39	rone	

Key Performance Indicators Applied to Internet Access (Copper)						
Package	KPI name	Measurement method	KPI value	Target value for quarter		
			Required Statistics and description	Q1	.a. Set talac for quarte	
		Mbps	The highest 95 % of download speed	6.44		
			The lowest 5 % of download speed	0.61	None	
			The mean value of download speed	6.15		
			The median value of download speed	6.48		
	Data Transmission Speed		The standard deviation of download speed	2.74		
B	Data Transmission Speed		The highest 95 % of upload speed	2.84		
10 MB			The lowest 5 % of upload speed	0.05		
0			The mean value of upload speed	2.7		
7			The median value of upload speed	0.37		
			The standard deviation of upload speed	12.27		
	Unsuccessful Data Transmission Ratio	Percentage %	Percentage of unsuccessful data transmission (in \mathbf{x}^{10-3})	cannot be provided	None	
	Delay (One-way transmission time)	Time	The mean values of the delay (in milliseconds)	58.01	None	
			The standard deviation of the delay (jitter) (in milliseconds)	239.65		
		Mbps	The highest 95 % of download speed	9.17		
			The lowest 5 % of download speed	0.7	None	
			The mean value of download speed	8.74		
	Data Transmission Speed		The median value of download speed	8.21		
			The standard deviation of download speed	5.06		
20 MB			The highest 95 % of upload speed	4.4		
			The lowest 5 % of upload speed	0.06		
			The mean value of upload speed	4.19		
			The median value of upload speed	0.64		
			The standard deviation of upload speed	12.76		
	Unsuccessful Data Transmission Ratio	Percentage %	Percentage of unsuccessful data transmission (in \mathbf{x}^{103})	cannot be provided	None	
	Delay (One-way	Time	The mean values of the delay (in milliseconds)	53.56	None	
	transmission time)	Tille	The standard deviation of the delay (jitter) (in milliseconds)	244.26		

Thank you!

